

epati

QoS - Bandwidth Management
Product: Antikor v2 - Next Generation Firewall
Guides

www.epati.com.tr

QoS - Bandwidth Management

It is used to determine the priority order of Ethernet packets (audio, video, etc.).



QoS - Bandwidth Management

#	Name	Type	CIDR Mask	Bandwidth	Transactions
1	10 Mb Limit Download	Download	32	10.00 Mbit/s	<input type="button" value="Edit"/> <input type="button" value="Delete"/> <input type="button" value="Queues"/>
2	Application Security Limiting	AppID - IPS	32	2.00 Mbit/s	<input type="button" value="Edit"/> <input type="button" value="Delete"/> <input type="button" value="Queues"/>
3	VOIP Priority	Download	32	10.00 Mbit/s	<input type="button" value="Edit"/> <input type="button" value="Delete"/> <input type="button" value="Queues"/>

New Record

QoS - Bandwidth Management - New Record ✕

Name A

Type ▼ ☰

CIDR Mask 0 - 32

Bandwidth Mbit/s

FIELD	DESCRIPTION
Name	Enter the name to be given to the bandwidth. Selection will be made using the name given in QoS rules.
Type	One of the Download, Install, or AppID - IPS types is selected. The selected values can be used in download and install QoS rules, while APPID - IPS is used in Application Security rules and IPS rules.
CIDR Mask	It is a bit value to determine the IP range to which QoS is applied.If the 32 bit value is entered, each client can use the specified QoS speed.
Bandwidth	It is the internet speed capability that each client can use.
Description	Clients can enter a description.

ePati Cyber Security Technologies Inc.
Mersin Universitesi Ciftlikkoy Kampusu
Teknopark Idari Binasi Kat: 4 No: 411
Zip Code: 33343 Yenisehir / MERSIN / TURKIYE

www.epati.com.tr
info@epati.com.tr
+90 324 361 02 33
+90 324 361 02 39

